



kramer

BC-1X

1 Coax RG-6 Super High-Resolution Bulk
Cable

| 3G HD-SDI - BNC



Kramer's BC-1X is a super high-resolution RG-6 style coaxial cable perfect for long distance composite and HD-SDI runs that require precision performance with analog or digital video signals

FEATURES

Quality Construction - 18AWG solid center conductor and dual shield design consisting of aluminum braid and dual aluminum Mylar foil. Rugged and flexible with low attenuation

Universal Compatibility - Compatible with Kramer's compression connectors as well as typical crimp systems

Length - Available in reels of 100/300m (328/984ft)



kramer

TECHNICAL SPECIFICATIONS

| | |
|----------------------|---|
| CONDUCTORS | Material Bare copper Construction 18AWG (1/18) Diameter 1.02 ±0.005mm |
| INSULATION | Material Skin foam Nom. Thickness 1.77mm Diameter 4.57 ±0.15mm |
| SCREENING | Material Dual-foil/mylar Coverage ≥125% |
| OVERALL SHIELD | Material Aluminum wire Construction 34AWG Coverage ≥61% |
| JACKET | Material PVC Nom. Thickness 0.76mm Color Dark gray Outer Diameter 6.95 ±0.19mm |
| ELECTRICAL | Rated Voltage 300V Rated Temperature 80°C DCR (20°C) 152Ω/1000m Capacitance (20°C) 53.pF/m SRL (20°C) -20dB Impedance (20°C) 75 ±5Ω Attenuation (20°C) 0.3 dB @1 MHz, 0.6 dB @ 5 MHz, 0.8 dB @ 10 MHz, 1 dB @ 20 MHz, 1.6 dB @ 50 MHz, 1.8 dB @ 71 MHz, 2.1 dB @ 100 MHz, 2.4dB @ 135 MHz, 2.8 dB @ 180 MHz, 2.9 dB @ 200 MHz, 3.4 dB @ 270 MHz, 4.5 dB @ 400 MHz, 5.8 dB @ 750 MHz, 6.8 dB @ 1000 MHz, 8.8 dB @ 1500 MHz, 12.9 dB @ 3000 MHz Velocity of Propagation (NVP) (20°C) 82% |
| STANDARDS COMPLIANCE | UL/cUL CL2 CSA FT4 RoHS 2011/65/EU |



kramer

CONFIGURATIONS

| | |
|------------|-------------------------|
| BC-1X-100M | 1 Coax: RG-6 Bulk Cable |
|------------|-------------------------|

| | |
|------------|-------------------------|
| BC-1X-300M | 1 Coax: RG-6 Bulk Cable |
|------------|-------------------------|
