ST630(P)



Mounting Pattern 75 x 75, 100 x 100mm



Max Load 80lb (36kg)

SMARTMOUNT.

Tilt Wall Mount

FOR 10" TO 29" DISPLAYS

The SmartMount® Tilt Wall Mount series offers the most versatile installation features and mounting options. Quickly and easily adjust the viewing angle without the use of tools. Security screws provided in the ST630 model deter tampering and theft. The display can now simply be installed by a single person with the Hook-and-Hang™ system. The Easy-Glide™ adaptors hook onto the wall plate for an overall quick, simple and secure installation.

- Accommodates 75 x 75 or 100 x 100mm VESA® mounting patterns
- Adjustable 15° forward tilt and -5° backward tilt for finding the optimal viewing angle
- Tilt angle locks into place with simple tightening of thumbscrew
- Display is positioned only 1.58" (40mm) from wall for a low-profile application
- Display adaptor simply slides into the wall plate for quick and easy installation
- Includes all necessary wall and display attachment hardware
- Integrated security options available
- Design is UL listed and tested to four times stated load capacity
- For mounts requiring theft resistant hardware, installed with security tool (included), please purchase ST630
- For mounts requiring standard hardware, installed with a Philips screwdriver, please purchase ST630P



Quickly adjust your viewing angle without tools

Mounts to wood stud, concrete, cinder or breeze block

HOOK-AND-HANG™ INSTALLATION



+15°/-5° of tilt for versatile viewing angles.



Comes in color packaging with included installation hardware and easy to follow instructions.



Please visit peerless-av.com/en-us/patents for patent information.

ST630P SmartMount® Tilt Wall Mount for 10" to 29" Displays - Standard Models ST630 SmartMount® Tilt Wall Mount for 10" to 29" Displays - Security Models

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
ST630(P)	6.61" x 6.20" x 1.58"-2.23" (168 x 157 x 40-57mm)	2.20lb (1.00kg)	80lb (36kg)	Scratch Resistant Fused Epoxy	Semi-Gloss Black

Package Specifications

	PACKAGE SIZE (W x H x D)	ACKAGE SIZE (W x H x D) PACKAGE SHIP WEIGHT PACKAGE UPC CODE		GE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
ST630(P)	9.38" x 2.90" x 8.25" (238 x 74 x 210mm)	2.8lb (1.3kg)	ST630: ST630P:	735029236627 735029236641	Wall Mount, Wall and Display Installation Hardware, Installation Instructions	1

Accessories

ACC215: ACC2X1: 2-pack Metal Stud Fastener Kit VESA® 200 x 100mm Adaptor Plate ESHV models:

AV Wall Shelves


IBA4-W:


Easy Mount Recessed Low Voltage Cable Plate


IBA5-W:


Recessed Low Voltage Media Plate with Duplex Surge Suppressor

All dimensions = inch (mm)









Architect Specifications

The SmartMount® Tilt Wall Mount shall be a Peerless-AV model ST630(P) and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV EMEA

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV Latin America

Ave de las Industrias 413 Parque Industrial Escobedo Escobedo, N.L., Mexico 66062

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

