

C3-340 CORIO®matrix is based on TV One's exclusive CORIO®2 technology and provides high quality modular video matrix switching using CORIO®softswitch, which provides an industry first firmware based video routing, switching and video conversion platform. 16 AV module slots are available. Additional DVI-U or 3G-SDI modules can be added later.

By choosing scaled output modules, the CORIO®matrix also provides Up, Down and Cross conversion between a variety of analog and digital video formats thru 3G-SDI. The modules selected determine what format will be accommodated and the matrix size. Signal parameters of the incoming video may be adjusted. All settings are stored in non-volatile memory and are retained even when power is switched off.

All the functions can be controlled via serial connection via RS-232 or IP. Windows software is provided for both video and audio routing and setup of the router and can be used as the main control interface if desired. Third party controllers using the built-in command line interface easily permits a wide choice of control options. The unit is housed in a standard 4RU rackmount case and features an optional redundant hot swappable internal PSU and power inlet.

Advanced Features

The CORIO®matrix includes advanced Digital Flicker Elimination circuitry and high 4:4:4 full bandwidth sampling rate ensures crisp, clear images, while full bandwidth chroma sampling ensures faithfully reproduced, high resolution colors. Pixel Level Motion Adaptive Diagonal Interpolation and Noise Reduction ensures high quality de-interlacing of PAL, NTSC and 1080i signals. 3:2 Pull-down ensures proper 24 fps film extraction from NTSC and 1080i sources.

Integral audio switching is provided to route audio from the DVI (HDMI-compatible) input or SDI input to the DVI and SDI outputs. An optional Audio Module can provide AES and analog or digital I/O breakout capabilities as well as audio delay and can link to our A2-7300 range of audio break-out units. Audio routing control is implemented in the Windows software and also available using the command line interface.

DVI-U

The DVI-U universal interface utilizes a single DVI-I connector to provide the following signal formats: HDMI, DVI-I, plus analog YUV, YPbPr, RGBHV, RBBS, RGsB, Y/C and Composite Video. A variety of adapters are available to convert from DVI-I to other connectors.



Standard Front Panel

Key Features of the C3-340

- DVI-U Inputs/Outputs: (HDMI/CV/YC/RGB/YPbPr)
- SDI Inputs/Outputs: (SD/HD/3G-SDI)
- High Resolution Inputs/Outputs:
 - Analog: PC to 2048x2048, HDTV to 1080p/60
 - DVI: PC to 1920x1200, HDTV to 1080p/60 w/EDID
 - SDI: SD, HDTV to 1080p/60
- HDMI-Compatible Input & Output with HDCP
- Automatic Incoming Resolution Detection
- 4:4:4 Full Bandwidth Sampling
- Video Signal Parameter Adjustments
- Horizontal alignment on Analogue PC Inputs
- Integral Audio Routing
- Audio de-embed/embed for SDI and DVI/HDMI
- Interfaces: RS-232, USB, IP
- Command Line Interface - Third Party Control Use
- 4RU Frame Size
- Modularity Provides Flexible I/O

Scaler Modules Provide

- Seamless Cross Format Matrix Switching
- Available with Up-Down-Cross Conversion
- Diagonal Interpolation
- Noise Reduction for PAL, NTSC & Analog 1080i In
- Motion Compensation & 3:2 Pull-down

Options

- Audio Module with AES Out and Adjustable Delay
- Digital & Analog Audio Breakout Boxes
- Redundant Hot Swappable Power Supplies
- Rear Rackmount Supports
- DVI-U Adapters (DVI to other connectors)

Future Planned Options

- HDBaseT Modules

DVI-U Modules

The system features the following types of modules for the inputs and outputs. All modules only use 1 AV Slot.

- DVI-U Universal Input Module - 2 Inputs
- DVI-U Universal Scaling Output Module - 2 Outputs

The DVI-U output module with scaling allows any input to be converted to any of the DVI-U formats on the output. The high resolution DVI-U outputs are selectable as virtually any PC or HDTV resolution.

SDI Modules

- 3G/HD/SD-SDI Input Module - 2 Inputs
- HD/SD-SDI Input Module - 4 Inputs
- 3G/HD/SD-SDI Output Scaling Module - 2 Outputs

The output module with scaling allow any input to be converted to SD-SDI, HD-SDI or 3G-SDI on the output.

Monitoring Module

A single monitoring card allows the inputs and outputs to be viewed on 1 or 2 outputs for signal verification. Embedded audio signals can be monitored along with source and destination identification. A separate DVI-U and 3G/HD/SD-SDI version of this module is available.

Audio Interfaces

The optional CM-AUD-8IN-8OUT Audio Interface Module allows connection to any of the following optional external breakout units via HD-44 Connector.

- A2-7312 Converts AES-3id I/O to 16x BNC Connectors
8x AES-id In and 8x AES-3id Out
- A2-7302 Converts AES-3id I/O to 16x XLR Connectors
8 AES Stereo In and 8x Stereo Out
- A2-7342 Converts AES-3id I/O to 16x XLR Connectors
4x Analog Stereo In & 4x Analog Out
- A2-7322 Converts AES-3id I/O to Analog Stereo on
Terminal Blocks, 8x Analog Stereo In and 8x Analog
Stereo Out, Balanced or Unbalanced

Future Modules

Additional types and formats of Video, Audio and Data Modules will be added in the future.

Main Chassis

C3-340-1001 Main Chassis w/Blank Front Panel

- 16 Slots available for Video/Audio Modules
- 3 Slots available for Possible Future Data Modules
- Up to 32 I/O for DVI, HDMI, 3G-SDI, RGB/YPbPr
- Up to 60 I/O for HD/SD-SDI using all 4x Input Modules
- Single Power Supply
- Interfaces for RS-232, USB, IP

Input Modules

CM-DVIU-2IN 2x via DVI-I Connectors

CM-3GSDI-2IN 2x (3G/HD/SD-SDI) via BNC

CM-HSDSI-4IN 4x (HD/SD-SDI) via BNC

Scaling Output Modules

CM-DVIU-XSC-2OUT 2x via DVI-I Connectors

CM-3GSDI-XSC-2OUT 2x (3G/HD/SD-SDI) via BNC

CM-HSDSI-XSC-4OUT 4x (HD/SD-SDI) via BNC

Note: Full A-to-D or D-to-A, Format and Framerate Conversion is provided with Scaling Output Modules.

Additional Modules

CM-DVIU-MON-2Out DVI Monitoring Module

CM-3GSDI-MON-2Out* SDI Monitoring Module

CM-AUD-8IN-8OUT Audio Interface Module

8x In & 8x Out via HD-44 Connector

CM-4RPS Redundant Hot Swappable Power Supply

Optional DVI-U Adapters

ZDH2050 Composite Video Adapter

DVI-I Male to BNC Female

ZDB2048 YC (S-Video) Adapter

DVI-I Male to 2-BNC Female

ZDS2046 YC (S-Video) Adapter

DVI-I Male to 4-Pin Mini-Din Female

ZDH2040 Analog PC Adapter

DVI-I Male to HD-15 Female

ZDB2038 Analog RGBHV Adapter Cable

DVI-I Male to 5-BNC Female – 1.5' (0.5m)

ZDB2044 YPbPr/YUV Adapter Cable

DVI-I Male to 3-BNC Female – 1.5' (0.5m)

ZDB2042 YPbPr/YUV Adapter

DVI-I Male to 3-RCA Female

CMD1939 HDMI Adapter

DVI-I Male to HDMI Female

Specifications

<p>Computer Inputs</p> <p>Digital DVI Up to 28 via DVI-U (HDMI & HDCP compatible)</p> <p>Analog Up to 30 via DVI-U</p> <p>Analog Format RGBHV, RGBS, RGsB, YPbPr</p> <p>Analog Sync TTL Level, 10KΩ, Pos or Neg</p> <p>RGB Level Range 0.5-2.0 Vp-p</p> <p>Scan Rate Detection Automatic</p> <p>Analog Signals PC to 2048x2048, HD to 1080p60</p> <p>DVI Signals PC to 1920x1200, HD to 1080p60</p> <p>Max Horiz Scan Rate 150kHz</p> <p>Computer Compatibility PC, Workstations</p>		<p>Video Inputs</p> <p>Television Standards NTSC, PAL, PAL-M/N, SECAM</p> <p>Composite Video Up to 28 via DVI-U</p> <p>YC (S-Video) Up to 28 via DVI-U</p> <p>YUV /YPbPr Up to 28 via DVI-U</p> <p>SD/HD-SDI Up to 56 via BNC</p> <p>SD/HD/3G-SDI Up to 28 via BNC</p>	
<p>Computer Outputs</p> <p>DVI Signals Up to 28 via DVI-U (HDMI & HDCP compatible)</p> <p>Analog Up to 24 via DVI-U</p> <p>Analog format RGBHV, RGBS, RGsB, YPbPr</p> <p>R-G-B Level 0.7 Vp-p</p> <p>DVI Signals PC to 1920x1200, HD to 1080p60</p> <p>Analog Signals PC to 1920x1080, HD to 1080p60</p> <p>Vertical Refresh Rate Any to 250Hz</p> <p>Size and Position User Adjustable</p> <p>Settings Memory Non-Volatile</p> <p>Conversion Technology Proprietary – CORIO®2</p> <p>Color RGB 24-bit 4:4:4 YPbPr 20-bit 4:2:2</p> <p>Max. Sampling Rate 162MHz</p> <p>Firmware Memory Flash, Upgradeable via micro-SD</p> <p>De-Interlacing Pixel-level Motion Adaptive, Diagonal Interpolation, Noise Reduction.</p> <p>Video Comb Filter Adaptive</p> <p>Film (NTSC, 1080i) 3:2 Pull-down</p> <p>Video Adjustments Contrast, Brightness, RGB Gamma</p>		<p>Video Outputs</p> <p>Television Standards NTSC, PAL, PAL-M/N, SECAM</p> <p>Composite Video Up to 28 via DVI-U</p> <p>YC (S-Video) Up to 28 via DVI-U</p> <p>YUV /YPbPr Up to 28 via DVI-U</p> <p>SD/HD-SDI Up to 56 via BNC</p> <p>SD/HD/3G-SDI Up to 28 via BNC</p>	
<p>Audio support</p> <p>De-embed/embed SDI & HDMI-I/O via DVI with optional audio interface module</p> <p>Delay optional audio interface module</p>		<p>3G/HD/SD-SDI</p> <p>SMPTE259M-C 270Mbps < 0.1UI jitter</p> <p>(SD-SDI Video) 525/625Line</p> <p>SMPTE292M 1.485/1.4835Gbps < 0.2 UI jitter</p> <p>(HD-SDI Video) 720p, 1035i, 1080i, 1080p</p> <p>SMPTE424M 2.97/2.967Gbps < 0.3 UI jitter</p> <p>(3G-SDI Video) 1080p 60/59.94</p> <p>SMPTE272M-2004 8 Stereo 24bit Audio Channels</p> <p>(SD-SDI Audio)</p> <p>SMPTE299M-2004 8 Stereo 24bit Audio Channels</p> <p>(3G/HD-SDI Audio)</p> <p>Note: Video & Audio Support Only</p>	
<p>HD Video Resolutions supported (DVI, YPbPr, SDI)</p> <p>720p (1280x720) 23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz</p> <p>1035i (1920x1035) 59.94, 60Hz</p> <p>1080i (1920x1080) 50, 59.94, 60Hz</p> <p>1080p (1920x1080) 23.98, 24, 25, 29.97, 30Hz</p> <p>1080p (1920x1080) 50, 59.94, 60Hz</p>		<p>Control Methods</p> <p>USB via Rear Type B connector</p> <p>RS-232 via D9 Female Connector</p> <p>IP Interface RJ45 Connector</p> <p>Warranty</p> <p>Limited Warranty 5 Years Parts and Labor</p> <p>Regulatory Compliance</p> <p>Main unit FCC, CE, RoHS</p> <p>Mechanical</p> <p>Size (H x W x D) 7.0" x 19.0" x 13.1" 178 x 482 x 334mm</p> <p>Weight (Net) Approx. 15Kg (33 lbs) (with redundant PSU option)</p> <p>Environmental</p> <p>Operating Temperature 0° to +40° C (+32° to +104° F)</p> <p>Operating Humidity 10% to 85%, Non-condensing</p> <p>Storage Temperature -10° to +70° C (+14° to +158° F)</p> <p>Storage Humidity 10% to 85%, Non-condensing</p> <p>MTBF Approximately 35,000 hours</p> <p>Power Requirement</p> <p>Internal Power Supply 110v to 240v auto-detecting</p> <p>Redundancy Optional Internal Hot Swap PSU</p> <p>Accessories Included</p> <p>1x Operations Manual</p> <p>1x Power cable US, UK, Euro or AU</p> <p>Control Software Downloadable from Website</p> <p>Optional Accessories</p> <p>See list above and check website for latest list</p>	

Note: Preliminary Specifications Only – Subject to Change

Rear Panel Views

Eight Input DVI-U, four 3G-SDI and four HD-SDI inputs
Eight input/eight output AES audio card
Eight Scaling Output DVI-U, four scaling 3G-SDI Outputs
Two non-scaling DVI-U outputs and
Dual DVI-U monitoring card



32 HD-SDI input, 32 non-scaling HD-SDI output Configuration



Front Angle View

